



# LNA 6901

## LOW NOISE AMPLIFIER 9 KHZ TO 1 GHZ



- **Wide band**
- **High gain**
- **Low noise figure**
- **Significantly enhancing the low level performance**

The LNA 6901 is a low noise amplifier with typ. 28 dB of gain covering the nominal frequency range 9 kHz to 1 GHz and can be used up to 2 GHz. With its high gain and low noise figure, it will significantly increase the sensitivity of virtually all spectrum analyzers and other RF measuring instruments. All measuring instruments have a 'noise figure', which is a measure of how good the instrument is at measuring low level signals, the lower this figure, the better, although the lowest signal level will still be governed by the measurement bandwidth. A typical spectrum analyzer may have a noise figure of 20 dB or more, whereas a typical receiver may have a noise figure of 10 dB. The preamplifier has a noise figure of typical 2.8 dB, significantly enhancing the low level performance of such instruments, enabling signals that were previously masked by noise to be seen.

The low noise amplifier can be connected directly to the RF input (N) of the spectrum analyzer or EMI-receiver. If the LNA 6901 is used with the Teseq receiver SCR 35xx/SMR 45xx, the power supply is provided directly by the receiver via the cable LE 237. Alternatively the power supply unit PSU 6000 can be used.

### Technical specifications

Frequency range:	9 kHz to 1 GHz (nominal range)
	9 kHz to 2 GHz (utilizable range)
Gain:	typ. 28 dB
Gain flatness:	±1 dB
RF-Input:	N - female, 50 Ω (optional N-male)
RF-Output:	N - male, 50 Ω (optional N-female)
VSWR (input):	<1.5
Noise figure:	typ. 2.8 dB (at 25°C, 100 MHz)
1 dB-compression (output):	+8 dBm
Intercept point IP3 (output):	typ. +25 dBm
Max. input (linear):	-20 dBm (87 dBμV)
DC-power supply:	11 to 15 V
DC-current:	approx. 100 mA
DC-connector:	ODU-female, plus on inner conductors
Operating temperature range:	0° to 40°C
Storage temperature range:	-20° to 60°C
Size (W x D x H) (without connectors):	27 mm x 50 mm x 27 mm
Size (W x D x H) (including connectors):	28 mm x 95 mm x 27 mm
Weight:	approx. 127 g

**Teseq GmbH**  
 Landsberger Str. 255 · 12623 Berlin · Germany  
 T +49 30 56 59 88 35 F +49 30 56 59 88 34  
 desales@teseq.com [www.teseq.com](http://www.teseq.com)

© July 2013 Teseq®  
 Specifications subject to change without notice.  
 Teseq® is an ISO-registered company. Its products are designed and manufactured under the strict quality and environmental requirements of the ISO 9001. This document has been carefully checked. However, Teseq® does not assume any liability for errors or inaccuracies.